



Dimensions	310mm x 310mm x 500mm (h)		12.2in x 12.2in x 19.69in (h)	
Weight	21,4 kg		47,2 lb	
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz	
Current Consumption	2,9 A		4,4 A	
Compressor Power	1/3 HP			
Power Consumption (Cooling)	440 W	1500 Btu/h		
Power Consumption (Heating)	400 W	1365 Btu/h		
Cooling Capacity *	870 W	2975 Btu/h		
Min and Max Water Flow	600 l/h - 800 l/h	159 Usgal/h - 211 Usgal/h		
Air Flow	215 m³/h	7600 CFH		
Maximum Exchanger's Pressure	0,6 bar	8,7 PSI		
Ambient Temperature Range	5°C - 38°C	41°F - 100°F		
Certification	CE			
Protection Grade	IPX4			

\* the value reported refers to the following condition: room temperature 30°C (86°F), water temperature 25°C (77°F)

Material:	Drawing: TK 2000 – technical data		
Thickness:	File: TK_2000_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1:6	Date: 02/10/2015
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 <a href="http://www.tecoonline.com">http://www.tecoonline.com</a>		
	Drawer: Matteo		

AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ARCHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES.WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.

Drawer: Modify: