



Voltage-Frequency	115V - 60Hz	
Current Consumption (Cooling)	2,2 A* (2,3A**)	
Current Consumption (Heating)	2,5A***	
Power Consumption (Cooling)	200 W*	
Power Consumption (Heating)	300 W***	
Cooling Capacity	410 W*	1400 Btu/h *
Dimensions	310mm x 310mm x 416mm (h)	12.2in x 12.2in x 16,38in (h)
Weight	16,5 kg	36,4 lb
Min and Max Water Flow	500 l/h - 800 l/h	132 Usgal/h - 211 Usgal/h
Air Flow	155 m³/h	5475 CFH
Maximum Exchanger's Pressure	1 bar	14,4 PSI
Ambient Temperature Range	10°C - 38°C	50°F - 100°F
Water Temperature Range	5°C - 30°C	41°F - 86°F
Unit of measure of temperature	°F (also °C available on request)	
Protection Grade	IPX4	
Refrigerant	R290	
* reported value refers to the following condition: room temperature 30°C (86°F), water temperature 25°C (77°F)		
** reported value refers to the following condition: room temperature 38°C (100°F), water temperature 25°C (77°F)		
***reported value refers to the following condition: room temperature 30°C (86°F), water temperature 20°C (68°F) with 500 l/h water flow		
All data are approximate and may be changed without notice by TECO		

Material:	Drawing: TK500H Technical data - 115V 60Hz - R290		
Thickness:	File: TK_500H_technical_data		
Finishing:	Your code:	Code: TKC#XX20HF21_	
Volume:	Tol.	Scale: 1: 6	Date: 25/03/2021
Approved:	Via Gregorio Ricci Curbastro, 8 48124 Fornace Zarattini - RA - ITALY Tel. +39 0544 408333 Fax 280084 <a href="http://www.tecoonline.com">http://www.tecoonline.com</a>		
	Drawer: Giulia		

AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ACHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES.WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.

Drawer: Giulia Modify: